

# specifications

Ice Merchandiser				Outside Dimensions			Glass Door	Approx. Wt. <sup>①</sup>		Refrigeration	Amperage	
Models	No. of Doors	Capacity		Width	Depth <sup>②</sup> <sup>③</sup>	Height	Width x Height	Cold Wall	Auto Defrost	Compressor 115/1/60	Cold Wall	Auto Defrost <sup>④</sup>
		Cu. Ft. (approx.)	Bags* (7 lb.)									
30C 30A	1	30	80 75	36"	30"	76-1/2"	28" x 47"	330	355	1/4 hp	4.7	5
40C 40A	1	40	165 160	50-1/2"	30"	76-1/2"	28" x 47"	380	405	1/3 hp	6.2	6.9
65C 65A	1	65	260 215	64"	35-1/2"	76-1/2"	28" x 47"	455	490	1/3 hp	6.2	6.9
60C 60A	2	60	265 260	73"	30"	76-1/2"	28" x 47"	530	565	1/2 hp	10.2	11.6
75C 75A	2	75	290 275	73"	35-1/2"	76-1/2"	28" x 47"	560	595	1/2 hp	10.2	12
85C 85A	2	85	345 325	84"	35-1/2"	76-1/2"	28" x 47"	610	650	1/2 hp	10.2	12
100C 100A	2	100	400 380	96"	35-1/2"	76-1/2"	28" x 47"	660	695	1/2 hp	10.2	12

Model Letter Suffixes:

"C" - Cold Wall

or

"A" - Automatic Defrost

① Shipping weight

② Add 3-1/2" for door and handle

③ Add 3" for condensate evaporator

④ Add 1.1 amps for condensate evaporator

## standard features

- Total steel cabinet construction
- Baked-on acrylic polyurethane, high solids, lead-free, enamel finish exterior
- Full 2-1/2"-thick, CFC-free, foamed-in-place polyurethane insulation in all walls and top with 3" bottom insulation
- Interior air flow ducts on automatic defrost models
- Triple-pane, tempered safety glass doors with self-closing hinges
- Illuminated interior
- R134a, low temperature, sealed condensing units
- Full top refrigeration cover
- Cold wall or automatic defrost refrigeration systems available on all models
- Condensate evaporator on automatic defrost models
- Five-year compressor warranty
- One-year parts warranty

\* Merchandiser storage capacity may vary due to type of ice, ice bag size differences and methods of loading.

## options

- Custom painted exterior
- Custom silk screening
- 220/1/50 voltage
- Heavy-duty refrigeration (automatic defrost models only)
- Reverse fan self-cleaning condensing unit

### note

- Glass door models are designed for use in stores where temperature and humidity are maintained at 75°F and 55% RH respectively.

Material and product improvement is a constant commitment at Leer Limited Partnership. These specifications are subject to change without notice and without incurring responsibility for previously sold merchandisers and components.



**LEER LIMITED PARTNERSHIP**

206 Leer Street, Box 206 • New Lisbon, WI 53950-0206  
 800-766-5337 • Ph: 608-562-3161 • Fax: 608-562-3203  
 Web Site: [www.leerlp.com](http://www.leerlp.com) • E-Mail: [info@leerlp.com](mailto:info@leerlp.com)



Printed In The USA  
 © LQA D03